

DESCRIPTION

Multicoloured wall covering consisting of 2/3mm flakes offered in Bright (full and pastel shades) Mineral and Metallic combinations to apply on base while still being wet. A protective varnish coat can also be applied.



ALTA DECORACION

ESCAMAS

RECOMMENDED APPLICATIONS

- Interior.
- Mainly applied as top coat or finish on FONDO ESCAMAS (Ref. 1254).
- Most type of surfaces used in construction (plaster, cement etc.) and wood previously primed with FONDO ESCAMAS (Ref. 1254).
- Especially recommended for public places (such as coffe-shops, restaurants, bingos, schools, shopping centres etc where an appealing, resistant, quick and long lasting finish is desired).
- Ideal in houses (halls, corridors, columns, bedrooms and walls where an attractive finish is desired).
- Gives a uniform finish. Alta Decoracion Barniz (protective varnish ref. 1263) can also be applied.
- To allow decoration suitability, there are 3 different types:
 - Viva (Bright): An attractive combination of pastel and full shades.
 - Metalica (Metallic): An attractive combination of metallic, micaceous and iridescent particles.
 - Mineral: An attractive combination of earth shades particles to give natural atmospheres.
- Gives a uniform finish. Alta Decoracion Barniz (protective varnish ref. 1263) can also be applied.

PROPERTIES

- Very easy to apply.
- Extremely quick to apply.
- Great performance, being 1 coat enough if applied as recommended.
- Conceals surface imperfections.
- Can be applied on any type of surface previously plastered, primed and anchored.
- Good resistance to sunlight.
- Alta Decoración Varnish num. 1263 can also be applied.
- Excellent resistance to being rubbed down and abrasion.
- Washable with detergents
- Dust-repellant.
- Quick drying.
- Outstanding adherence level.
- Odourless.
- Does not spread fire. M1 resistance.

PRODUCT DATA SPECIFICATION

- Nature: made of 3/4 mm multicoloured flakes.
- Appearance: Textured. Uniform.
- Gloss index (UNE-48026 at 85°): 7 +2%.
- Texture: very fine.
- Colours:
 - Viva: (Bright) 11 Combinations of full and pastel shades.
 - Metalica (Metallic): 6 combinations of metallic and iridescent particles.
 - Mineral: 10 attractive combinations of earth-like shades particles.
- See Alta Decoracion num 11 (ESCARCHA) samples. All colours are miscible at any proportion.
- Pigments: Highly resistant to sunlight micaceous, iridescent and metallic organic and inorganic.
- Density: 0,60 + 0,05 Kg./l.
- Approx. Performance per coat.
 - 4-6 m2/ Kg. Only one coat is necessary.
- Washability: Total.

APPLICATION SYSTEMS

- Thinner_ None, poject on FONDO ESCAMAS while being still wet.
- Tools: Thinning:
- Special spray guns:
- Special flakes spray gun (ref. 657048) None.
- Sagola 4950: None
- Special Flakes Rigo: None
- Kripxe SPG: None.
- Re-varnish (20° C, HR 60%):
 - Min. 6 hours.
 - Max. Unlimited.

NEW SURFACES PREPARATION

-Cement and plaster mortar:
-Prepare surface as per emulsion paints, plastering, cleaning and sandpapering as per FONDO ESCAMAS (ref. 1254) data sheet guidelines.

SURFACE RESTORATION

1. Remove off old paints completely.
2. Brilliant surfaces should be matted to ensure good adherence.
3. Check paint type and anchoring in painted surfaces to avoid incompatibilities. Remove off any dust or dirt before painting.
4. Cover surface imperfections with suitable putty of plaster (See Family 6 to help you choose the most suitable product to prepare surfaces).
5. Mildewed surfaces should be treated with Montolimp fungicide.
6. Should you need to apply on old paints, these should be of good quality.

APPLICATION

-Prime with Emulsión Fijadora (Ref.2370) or Fijamont (Ref.2360) should it be necessary. Apply Ibersat (Ref. 2630) or Tornado Satinado (Ref. 2600) after fixer if surface is too absorbent.
-Apply Selladora Sellalux (Ref.2340) on wood.
-Apply FONDO ESCAMAS ROCIO (Ref. 1254) similar to the chosen colour for ROCIO as per data sheet guidelines.
-Project flakes with blowing gun (ref. 7048 at 40 or 50 cm distance, with upward circular movements. The FONDO ESCAMAS should be wet in order to be applied (10 minutes after product preparation) It is advisable to apply product between 2 people: one priming and the other projecting. Choose areas of application or squares of 1,20 x 1,20 m. To avoid double coating between square lines or application areas, flakes should be projected at 20 cms distance.
-To avoid wasting product, clean the floor close to the working area and cover it with a plastic of 50 cm approx. This will help to recuperate flakes fallen while projecting. Put these flakes into plastic bag, not the gun, mix with remaining product to use again.
-Wait 6 hours after applying FONDO ESCAMAS + ROCIO. Brush surface with a hard brush to remove loose flakes. A very fine sandpaper can also be used to achieve a smoother texture.
-Apply Select Decoration Barniz Protector (protection varnish) in thin layers always in the same direction by lacquering roller. Use a brush for corners.

PROCESSES	Primer	Undercoat	Finish
OLD PAINTS IN GOOD CONDITION	Max:	IBERSAT+ FONDO ESCAMAS	ESCARCHA + BARNIZ ALTA DECORACION
	Std:	FONDO ESCAMAS	ESCARCHA
OLD PAINTS IN BAD CONDITIONS	Max:	IBERSAT+ FONDO ESCAMAS	ESCARCHA + BARNIZ ALTA DECORACION
	Std:	EMULSION FIJADORA O FIJAMONT	ESCARCHA
NEW CEMENT AND BY PRODUCTS	Max:	IBERSAT+ FONDO ESCAMAS	ESCARCHA + BARNIZ ALTA DECORACION
	Std:	EMULSION FIJADORA O FIJAMONT	ESCARCHA
DRY PLASTER AND BY PRODUCTS	Max:	IBERSAT+ FONDO ESCAMAS	ESCARCHA + BARNIZ ALTA DECORACION
	Std:	EMULSION FIJADORA O FIJAMONT	ESCARCHA
NEW WOOD AND BY PRODUCTS	Max:	IBERSAT+ FONDO ESCAMAS	ESCARCHA + BARNIZ ALTA DECORACION
	Std:	SELLADORA SELLALUX	ESCARCHA

NEW WOOD AND BY PRODUCTS

Max:	IBERSAT+ FONDO ESCAMAS	ESCARCHA + BARNIZ ALTA DECORACION
Std: EMULSION FIJADORA O FIJAMONT	FONDO ESCAMAS	ESCARCHA

MILDEWED SURFACES

Max:	IBERSAT+ FONDO ESCAMAS	ESCARCHA + BARNIZ ALTA DECORACION
Std: MONTOLIMP + EMULSION FIJADORA O FIJAMONT	FONDO ESCAMAS	ESCARCHA

GENERAL INFORMATION

- Apply suitable plaster or putty.
- Do not apply on wet or frosty surfaces caused by extremely cold night temperatures or when rain or frost has been forecast to avoid the binding properties to frost and lose product adherence, reducing and affecting product results in the short and long term.
- Apply at temperatures over 5° C.
- Apply on surfaces over 5° C.
- Do not apply at high temperatures or over reheated surfaces since this will dry product only superficially, not deeply and the final results and quality of product will be reduced.
- Product shelf life: 30 months from manufacturing date, provided is kept in original closed container, in a dry room, at temperatures between 5° C and 35° C maximum.
- The current EEC marketing merchansing laws and regulations must be observed and carried out at all times.
- Under the current EEC laws and regulations, norms indicated in container must be observed and carried out at all times.

SAFE AND SAFETY - ENVIROMENT

- Do not eat, drink or smoke when using product.
- If eye contact occurs, wash with plenty of fresh water.
- Toxical product if ingested.
- Keep away from children's reach.
- Do not empty waste into drains or water courses.
- Store product only in dry areas.

ALSO IN SOLVENT BASED PRODUCTS:

- Apply product in well-ventilated areas. In case if insufficient ventilation, wear suitable respiratory protective masks.
- Wear suitable mask or protective clothing when using spray gun or for the sandpapering and brushing of paint.
- Keep area to be painted well ventilated until complete drying of product.
- Do not ingest or inhale product. Avoid skin or eye contact. If eye contact occurs, seek medical attention immediately.
- Store product only in well ventilated, not-flammable areas.

NOTICE

The information contained herein, is only based on our current knowledge, laboratory tests and practical use under specific circumstances and objective decision. Due to the impossibility to give specific description for every different painting surface and being the nature conditions beyond our control, we are unable to guarantee the total repeatability in every concrete use.

The manufacturer and sales person do not assume any responsibility, unless a specific written agreement has been previously made, for the use of our products derived from the application of our products according to our recommendations, since these are beyond our control.

Due to the constant technical development, our recommendation do not relieve our costumers of the necessity to test our products, on their own responsibility, for suitability for the purpose envisaged, and checked that the information given harein has not been updated. The recommendations given herein sepersede previous ones regarding the same product.

MADE IN THE UE