

503050

01/02/2000

BARNIZ LADRILLO



DESCRIPTION

Water based transparent varnish, specially formulated for the protection of porous and absorbent surfaces.



IMPERMEAB. Y REVEST. FACHADAS

IMPERMEABILIZANTES

RECOMMENDED APPLICATIONS

- Applicable on any type of absorbent stony surfaces.
- Interior/exterior.
- For the protection of brick, natural and artificial stone, fibrecement etc.

PROPERTIES

- Protects varnished surfaces against atmospheric agents.
- Humidity proof.
- Allows surface transpiration.
- Good anchoring on dusty surfaces.
- Regulates porous surfaces.
- Does not alter original surface colour.
- Gives a mat finish when applied within recommended amount.
- Does not spread fire.
- Almost odourless.

PRODUCT DATA SPECIFICATION

- Nature: Ester acrylic aqueous dispersion.
- Appearance: Milky.
- Texture: Smooth
- Colour: Transparent.
- Specific gravity (ASTM D-1475-90): $1,01 \pm 0,05$ Kg./ l.
- Viscosity (Brookfield RVT spin 5 at 20 r.p.m. at 20° C): -40-80 Poises.
- Approximate performance per coat: 9-15 m²/ l.
- Drying (20° C HR: 60%):
- to touch: 1/2- 1 hour.

AFNOR: T. 30.003 - FAMILY I CLASS 7b2

APPLICATION SYSTEMS

- Thinner: water.
- Tools: Thinning.
- Brush: 3/5 part water per 1 part Varnish.
- Roller: 3/5 part water per 1 part Varnish.
- Aerographic spray gun: 3/5 part water per 1 part Varnish.
- Low pressure turbo: 3/5 part water per 1 part Varnish.
- Airless: 3/5 part water per 1 part Varnish.
- Airmix: 3/5 part water per 1 part Varnish.
- Repainting: (20° C, HR 60%):
- Minimum: 8 hours.
- Maximum: Unlimited.
- Cleaning: Water immediately after use.

NEW SURFACES PREPARATION

- Remove off any efflorescences, remains or foreign products by abrasive jet and neutralize alkaline surfaces.
- Extremely polished surfaces should be sanded to open pores.
- Cover surface imperfections with suitable plaster.
- Mildewed surfaces should be treated with Montolimp fungicide.

SURFACE RESTORATION

- 1.This product should only be applied on surfaces free of any paint trace and with open porous.
- 2.For old surfaces that comply with these requirements, proceed as per new surfaces.

APPLICATION

- Shake product until perfectly homogenized.
- Thinning: 3/5 parts of water per 1 part BARNIZ LADRILLO. The bigger the porous, is the less thinning needs. Excess of product may cause glossy areas.
- This product should not be applied at temperatures below 5° or any surfaces which have been in the sun.

PROCESSES	Primer	Undercoat	Finish
BRICK	Max:		
	Std: BARNIZ LADRILLO DILUIDO		BARNIZ LADRILLO DILUIDO
OLD PAINTS IN BAD CONDITIONS	Max:		
	Std: ELIMINAR ANTIGUAS PINTURAS	BARNIZ LADRILLO DILUIDO	BARNIZ LADRILLO DILUIDO
NATURAL OR ARTIFICIAL STONE	Max:		
	Std: BARNIZ LADRILLO DILUIDO		BARNIZ LADRILLO DILUIDO
DRY PLASTER AND BY PRODUCTS	Max:		
	Std: BARNIZ LADRILLO DILUIDO		BARNIZ LADRILLO DILUIDO
FIBRECEMENT	Max:		
	Std: BARNIZ LADRILLO DILUIDO		BARNIZ LADRILLO DILUIDO
SURFACES IN BAD CONDITIONS	Max:		
	Std: FIJADOR 2360 2370	BARNIZ LADRILLO DILUIDO	BARNIZ LADRILLO DILUIDO
MILDEWED SURFACES	Max:		
	Std: MONTOLIMP		BARNIZ LADRILLO DILUIDO+ MONTOPLAS

GENERAL INFORMATION

Use only fresh, clean water.

-Use suitable plastering materials for exteriors.

-Do not apply on wet surfaces which have been exposed to extreme cold temperatures at night nor overheated or when rain or frost have been forecast, since its adherence level may be seriously reduced in the short and long term of product.

-Do not expose container to extreme cold or hot temperatures.

-Do not add any water to remaining unused product in order to store it.

-Product shelf life: 30 months from manufacturing date, provided is kept in original closed container, in a dry room, at temperatures between 5° C and 35° C maximum.

-The current EEC marketing merchansing laws and regulations must be observed and carried out at all times.

-Under the current EEC laws and regulations, norms indicated in container must be observed and carried out at all times.

SAFE AND SAFETY - ENVIROMENT

Do not eat, drink or smoke when using product.

If eye contact occurs, wash with plenty of fresh water.

Toxical product if ingested.

Keep away from children's reach.

Do not empty waste into drains or water courses.

Store product only in dry areas.

ALSO IN SOLVENT BASED PRODUCTS:

Apply product in well-ventilated areas. In case if insufficient ventilation, wear suitable respiratory protective masks.

Wear suitable mask or protective clothing when using spray gun or for the sandpapering and brushing of paint.

NOTICE

The information contained herein, is only based on our current knowledge, laboratory tests and practical use under specific circumstances and objective decision. Due to the impossibility to give specific description for every different painting surface and being the nature conditions beyond our control, we are unable to guarantee the total repeatability in every concrete use.

The manufacturer and sales person do not assume any responsibility, unless a specific written agreement has been previously made, for the use of our products derived from the application of our products according to our recommendations, since these are beyond our control.

503050

BARNIZ LADRILLO

01/02/2000



Keep area to be painted well ventilated until complete drying of product.

Do not ingest or inhale product. Avoid skin or eye contact. If eye contact occurs, seek medical attention immediately.

Store product only in well ventilated, not-flammable areas.

Due to the constant technical development, our recommendation do not relieve our costumers of the necessity to test our products, on their own responsibility, for suitability for the purpose envisaged, and checked that the information given harein has not been updated. The recommendations given herein sepersede previous ones regarding the same product.

MADE IN THE UE