

503225

01/02/2000

# CONVERPLUS SECANTE LIQUIDO



## DESCRIPTION

Concentrated additive which added to MONTO solvent based products, reactivates their drying.



## PRODUCTOS PARA USO ESPECIFICO

## ADITIVOS

## RECOMMENDED APPLICATIONS

- Reactivates the drying of synthetic products such as Montosintético, Luxatín, Marisma, Férrum.
- Reactivates the drying of synthetic varnishes such as Barniz Sintético Universal, Veler Alta montaña.
- Reactivates the drying of White Spirit based products.

## PROPERTIES

- Permits easy addition by simple homogenization.
- Improves and reactivates the drying effect of those products to which is added.
- Does not modify colour or appearance of product to which is to be added.
- Compatible with White Spirit based products and systems.
- Reactivates the drying effect of enamels and varnishes.

## PRODUCT DATA SPECIFICATION

- Nature: Isociante solution.
- Appearance: Liquid.
- Colour: Transparent.
- Pigments: Free
- Specific gravity: 0,85 + 0,05 Kg./l.
- Addition:
- Minimum:
- Maximum: 15%

## APPLICATION SYSTEMS

- Thinner: As per product to be added to.
- Tools: thinning:
- Brush: As per product to be added to.
  - Roller: As per product to be added to.
  - Aerographic spray gun: As per product to be added to.
  - Airless: As per product to be added to.
  - Airmix: As per product to be added to.
- Repainting: (20° C, HR 60%):
- As per product to be added to:

## NEW SURFACES PREPARATION

Proceed as per product to be added to.

## SURFACE RESTORATION

Proceed as per product to be added to.

## APPLICATION

- Maximum dosification 20%.
- Follow product to which is to be added guidelines.

## PROCESSES

Primer

Undercoat

Finish

## GENERAL INFORMATION

-Follow product to which is to be added guidelines.

503225

01/02/2000

# CONVERPLUS SECANTE LIQUIDO



## SAFE AND SAFETY - ENVIROMENT

Do not eat, drink or smoke when using product.  
If eye contact occurs, wash with plenty of fresh water.  
Toxical product if ingested.  
Keep away from children's reach.  
Do not empty waste into drains or water courses.  
Store product only in dry areas.

### ALSO IN SOLVENT BASED PRODUCTS:

Apply product in well-ventilated areas. In case if insufficient ventilation, wear suitable respiratory protective masks.  
Wear suitable mask or protective clothing when using spray gun or for the sandpapering and brushing of paint.  
Keep area to be painted well ventilated until complete drying of product.  
Do not ingest or inhale product. Avoid skin or eye contact. If eye contact occurs, seek medical attention immediately.  
Store product only in well ventilated, not-flammable areas.

## NOTICE

The information contained herein, is only based on our current knowledge, laboratory tests and practical use under specific circumstances and objective decision. Due to the impossibility to give specific description for every different painting surface and being the nature conditions beyond our control, we are unable to guarantee the total repeatability in every concrete use.

The manufacturer and sales person do not assume any responsibility, unless a specific written agreement has been previously made, for the use of our products derived from the application of our products according to our recommendations, since these are beyond our control. Due to the constant technical development, our recommendation do not relieve our costumers of the necessity to test our products, on their own responsibility, for suitability for the purpose envisaged, and checked that the information given here in has not been updated. The recommendations given herein sepersede previous ones regarding the same product.

**MADE IN THE UE**